



Manual fidbox Software – Explanation and Guide

floor protector®

Safe from the Ground up.




Contents Overview

1. Program function overview - Software Version 3.6.2
2. Sync - sending data per E-Mail and archiving
3. Table - evaluation in data tables
4. Chart - analysis of **fidbox** measuring data
5. Compare Chart – using **fidbox** measuring data
6. Init **fidbox** –see separate manual for this section
7. Reports – see separate manual for this section
8. Delivery Note – reserved for FloorProtector support team
9. Handheld Tools – see separate manual for this section
10. Manual – available manuals for immediate access
11. Info –language, software version and identification of USB Stick Reader
12. Close – program exit



1. Program function overview Software Version 3.6.1



This screen appears immediately after the start of the **fidbox** program.

The **fidbox** software is available in German and English.

Choose your language setting by clicking the button “Info”.

Once you have selected the language, you can take advantage of the other buttons on the left side. All parts of the program, as well as reports and evaluations are then displayed in the selected language.



1. Program function overview Software Version 3.6.1














The program section “**Info**” provides information about the installed version of the software and the copyright information of this **fidbox** computer software.

- > 1 Connected Reader:
This identifies the USB reader with which you are working and its serial number (in this case it is 1011041)
- > 2 Language:
Select your language by using the drop down menus
 - > U.S. Version – This is intended for the North American market only
- > 3 Software version:
The version is: 3.6.2



1. Program function overview Software Version 3.6.1

 Sync	→	Synchronisation of fidbox measuring data from Handheld or USB Reader with Computer, archiving and sending data per E-Mail
 Table	→	Table analysis of fidbox measuring data
 Chart	→	Chart analysis of fidbox measuring data
 Compare Chart	→	Chart comparison analysis of two different fidbox measuring data
 init fidbox	→	Find fidbox, Read-out and adjust fidbox setting
 Report	→	Reports , producing and evaluating of fidbox measuring data
 Delivery Note	→	Reserved for FloorProtector support team
 Handheld Tools	→	Software Update for Handhelds
 Manual	→	Different manuals for immediate access
 Info	→	Program information for version and language setting D / EN
 Close	→	Close the program and return to system level



1. Program function overview Software Version 3.6.1




Important Notice

If you read the measurement data file of a **fidbox** with the same serial number several times and save the readings to your computer each time, the original stored measuring data file on your computer will be "**overwritten**".

To avoid this, you can rename the existing data file manually. It is essential that you write the new file name without spaces i.e. **Hotel-lobby-01-2010.xml**. Contact us if you have any questions.



2. Sync – Sending data per E-Mail and archiving



Sync is used to collect data from the handhelds, to send data per E-Mail and to archive required data.

All **fidbox** data files stored on your computer can be easily and quickly sent as an E-Mail with a click of the mouse e.g. to floorprotector for an analysis of the data.

All **fidbox** files stored on the computer will be shown in the “Enclosures“. These data files can now be individually selected. Each blue marked file has been selected for sending.

The displayed data file shows the name / serial number of the read **fidbox** with a supplementary date showing the time of being placed into memory.

Continue on the next page....





2. Sync – Sending data per E-Mail and archiving

Sync | **Email** | Archive

eMail Program: OUTLOOK

Address:
To: office@floorprotector.at

Step 1:

Click on the selection tab "Email". In the selection window click on "**E-Mail Program**" choose your actual E- mail program for sending E-Mails. Enter the address of the recipient in the box "**E-Mail Address**".

Details

Mounting Place: Hotel Lobby

Mounting Date: 08.06.2012 02:18:30

Name: Parquet Layer woodprofi

Comment: Inspection interval

Other:

Step 2:

Enter in each field the necessary information that you want to share with the recipient.

Attachments

<input checked="" type="checkbox"/>	ADMIN_E004200910000221 06/08/2012 11:12:30
<input checked="" type="checkbox"/>	E004201104000003_fidbox Testmessdaten 05/30/2012 13:55:15
<input type="checkbox"/>	fidbox-123456-Hotel-2012 04/17/2012 10:55:01
<input type="checkbox"/>	fidbox-987654-Hotel-2012 04/17/2012 11:21:08

Step 3:


Mark the desired **fidbox** data file (check mark) to be sent.

Continue on the next page ...





2. Sync – Sending data per E-Mail and archiving



Step 4:


Finally, click the **"send email"** button which is found on the bottom right of the screen display. The E-Mail is on its way.

Eventual information prompts from Windows will confirm the successful transmission of your E-Mail.

Eventual queries and usage rights from Windows should be confirmed in accordance with the instructions or as you prefer.



2. Sync – Sending data per E-Mail and archiving



Archiving fidbox measuring data

All **fidbox** measuring data files stored in memory on the computer can be filed in the archive quickly and easily with one click.

A regular archiving will give clarity regards the actual measured data files, especially if there are many **fidbox** data files to be managed on the computer.

A **fidbox** measuring data file can be reactivated from the archive at any time for an evaluation.

Continue on the following page...





2. Sync – Sending data per E-Mail and archiving



Step 1:

Click on the selection tab **“Archive”**.

All currently stored fidbox data files will be shown in the display **“archive”** (sorted alphabetically). You can now individually select these measuring data files. Each selected data file for archiving is indicated with a tick mark.

The displayed data file shows the name/serial number of the read fidbox together with a date and time of saving to memory.

Continue on the next page ...





2. Sync – Sending data per E-Mail and archiving



Step 2:

Choose whether you want to export the data for example to a disk, to a different hard drive, to a different folder or if you wish one or the other to be stored in the folder created in fidbox archive folder.


Step 3:

If you select “**Export**”, enter the desired drive specification of the destination folder in which you wish to archive the data to be stored and click “OK”. The selected fidbox measuring file data is then stored in the destination folder.

**Continue with the alternative –
”Archive” on the next page ...**



2. Sync – Sending data per E-Mail and archiving





Step 4:

A confirmation will appear after pressing the button **"Archive"**. The required fidbox measuring data files have been successfully moved to the archive folder.


Information:

The archived data has been routinely moved to the folder **C:\ProgramData\fidbox\Data\Archive** And can be retrieved from there at any time and put back into the “data-folder” using the copy and paste function.





2. Sync – Sending data per E-Mail and archiving




Continue with Close or make a new selection ...





3. Table – Evaluation in data tables



The **fidbox** measurement data file selected for measurement data analysis can be immediately displayed on the screen.

Chronologically, all available measuring data of the selected **fidbox** beginning with the most recent **fidbox** reading are shown in tabular form. Using the scrollbar on the side of the display, all available measured data can be viewed by upward and downward scrolling.

All red/blue colored single measurement values indicate reading infringements of higher or lower values than the pre-defined limitations.

The standard limitation values may be adjusted as desired for this display. Accordingly, the shown readings will adjust in regards to infringements of the higher or lower limitations.

Continue on the next page ...





3. Table – Evaluation in data tables

Step 1:

Click **“Select File”** and choose the desired **fidbox** measurement data file for evaluation.

Step 2: - Only if required

Select if required in the selection window “Unit“ for the desired temperature display “Celsius or Fahrenheit“. This means that all temperature-reading of (Celsius = factory setting) will be converted and accordingly shown.

Screen Display

Select File	E004201104102114 2/25/2013 5:53:08 AM			Unit:	Celsius
Substrate (T1) max. Temperature	26	Substrate (T1) min. Temperature	17	Floor Material Surface (T2) max. Temperature	26
Substrate (H1) max. rel. Humidity	60	Substrate (H1) min. rel. Humidity	45	Floor Material Surface (H2) max. rel. Humidity	60
				Floor Material Surface (H2) min. rel. Humidity	45

Step 3: - Only if required

Select if required in the selection window **“max. / min. Temperature and rel. Humidity”** the desired setting for the evaluation criteria and make the required changes using the arrow buttons on the side. This will mean that all subsequent evaluations will be shown with the temperature and relative humidity setting given in this display. **Deviations above the upper set values** will be shown in **“red”** and deviations **below the lower set values will be shown in “blue”**.

Continuation on the next page ...





3. Table – Evaluation in data tables

Select Filefidbox-123456-Hotel-2012 4/17/2012 10:55:01 AMUnit:Celsius

Substrate (T1) max. Temperature26Substrate (T1) min. Temperature17Floor Material Surface (T2) max. Temperature26Floor Material Surface (T2) min.17

Substrate (H1) max. rel. Humidity60Substrate (H1) min. rel. Humidity45Floor Material Surface (H2) max. rel. Humidity60Floor Material Surface (H2) min. rel.45

	Time	Substrate (T1) Temperature	Floor Material Surface (T2) Temperature	Substrate (H1) rel. Humidity	Floor Material Surface (H2) rel. Humidity
▶	4/17/2012 11:00:00 AM	29.40	26.90	26.90	26.97
	4/17/2012 5:00:00 AM	28.96	26.37	26.90	26.68
	4/16/2012 11:00:00 PM	29.02	26.52	26.93	26.68



Table display of measuring data

The stored individual measurement data of the selected **fidbox** measurement data file are shown in this table separately for each measurement sensor parquet and screed. .

- 1- Time

2- Floor Material Surface (T2)

3- Substrate(T1)

4- Floor Material Surface r.H. (H2)

5- Substrate r.H. (H1)
- Date and time of the measurement (display form mm:dd:jj - hour:min – AM/PM)

Temperature (°C) on the surface of the floor material

Temperature (°C) on the surface of the substrate

relative Humidity (%) on the surface of the floor material (measured capacitive)

relative Humidity (%) on the surface of the substrate (measured capacitive)

You can make as many changes in the display form as you wish. It has no effect on the stored original data.





3. Table – Evaluation in data tables



Continue with Program Exit or new selection ...





4. Chart – Analysis of fidbox measuring data



Screen Display



After the complete **synchronization** between the handheld and the computer (see Section 2) the **fidbox** measuring data can be immediately selected and analysed by clicking on the program selection button “**Diagram**”.

The progression of the whole measurement period can be viewed in understandable diagrams, separated by temperature levels (°C) and relative humidity (%).

Zooming in selected periods of time and movement of limits is possible at any time and without any impact on the originally stored data.

Continuation on the next page ...



4. Chart – Analysis of fidbox measuring data



Screen Display

Selection of **fidbox** data file, settings of limitations and display of measurement data.

Temperature Diagram (°C) with limitation value lines (red), divided in a timeline (date) and Temperature flow (°C). Display of both **fidbox** sensors.

Rel. Humidity (%) Diagram with limitation value line (rot), divided in a timeline (date) and flow of Rel. Humidity (%). Display of both **fidbox** sensors.

Continuation on the next page...



Chart



4. Chart – Analysis of fidbox measuring data

Step1:

Select the **fidbox** measuring data file desired for data analysis . All available **fidbox** measuring data files are displayed for selection in the scroll down menu. The desired **fidbox** data file can be selected by clicking on the data file and it is immediately displayed for analysis.

Screen Display

The screenshot shows a software interface for selecting data files. It includes a 'Select File' dropdown menu with the text 'fidbox-123456-Hotel-2012 4/17/2012 10:55:01 AM'. Below this is a 'Date From' field with a date selector set to '12.10.2008' and a 'Date to' field with a date selector set to '17.04.2012'. At the bottom, there are two input fields for 'Temperature High' (set to 26) and 'Temperature Low' (set to 17). To the right of these are two checked checkboxes: 'T1: Substrate' and 'T2: Floor Material Surface'. Further right is an 'Init:' dropdown menu set to 'Celsius'. Three red arrows are overlaid on the image: one points to the 'Select File' dropdown, and two point to the 'Temperature High' and 'Temperature Low' input fields respectively.

Step 2:

For the data analysis evaluation time period select "Date from" and "Date to" of the desired **fidbox** measuring data file. In the scroll down menu, the factory setting will display all available **fidbox** measuring data for selection. By clicking and selecting the desired date limitations (in calendar form) the desired date limitations are selected and immediately displayed for analysis.

Tip: Note that in the field "**Date from**" you must have an earlier date than in the field: "**Date to**".

Continuation on the next page ...



Chart



4. Chart – Analysis of fidbox measuring data

Select File:

Date From: to

Temperature High: Temperature Low:

☒ T1: Substrate ☒ T2: Floor Material Surface Init:

Screen Display

Step 3: - if desired

Click the scroll button “**temp high:**” or “**temp low:**” and set this to the desired temperature limitations (i.e. in °C), to which the data are to be analysed. If you call a **fidbox** measuring data file up for chart analysis, the temperature settings are displayed based on your selection as an upper or lower limit (red line limit). You always have the option to adjust the display to your liking and change it. The factory setting is: temp above 26 °C and below temp: 17 °C.

Step 4: - if desired

By activating or deactivating the display of a measuring sensor it can be shown or hidden. With a set tick mark (factory setting), the respective sensor measurement is presented as a graph in the display.

T1: Substrate sensor as a **green line__**

T2: Floor Material Surface sensor as a **black line__**

You always have the option to change this display to your liking.

Continuation on the next page...





4. Chart – Analysis of fidbox measuring data

Select File: fidbox-123456-Hotel-2012 4/17/2012 10:55:01 AM

Date From: 12.10.2008 to 17.04.2012

Temperature High: 26 Temperature Low: 17

☒ T1: Substrate ☒ T2: Floor Material Surface Init: Celsius

Screen Display

Conversion formula

°Celsius in °Fahrenheit

$$3,038 \text{ } ^\circ\text{F} = 1 \text{ } ^\circ\text{C}$$

$$1 \text{ } ^\circ\text{F} = 0,329 \text{ } ^\circ\text{C}$$

Step 5: - only if necessary

If required, choose in the selection window "Unit" of the desired fidbox to be evaluated, the desired temperature indicators "**Celsius / Fahrenheit**". This means that all temperature indicators (C = factory setting) are converted accordingly and then displayed in Fahrenheit.

Continuation on the next page ...




Chart

4. Chart – Analysis of fidbox measuring data

Diagram Analysis Temperature

Screen Display




Hide or conceal a measuring sensor
- see Step 4



4. Chart – Analysis of fidbox measuring data

Screen Display



Lower limitation value rel.
Humidity min. 45 %

Actually measured rel. Humidity
% at screed side - Sensor T1



Actually measured rel. Humidity %
at parquet side - Sensor T2

Upper limitation value
rel. Humidity max. 60 %



Hide or concealing a measuring sensor
- see Step 4

4. Chart – Analysis of fidbox measuring data



Bildschirmanzeige

Diagram section - Zoom


During the display of chart analysis, there is an additional help tool available. The possibility of enlarging a selected portion of the graphic display – as large as you wish.

As you are in the graphic display, press and hold the left mouse button and drag the zoom range (dashed line) to the desired size.

Close this zoom range again by pressing the right mouse button. Click **undo all zooms** in the **context menu** that appears



4. Chart – Analysis of fidbox measuring data



While the screen is the chart analysis, an additional tool is available and is called a **Context Menu** (right mouse button to activate). Select from the following options:

- **copy** – copy the screen to the clipboard
- **save Image as ...** - save the screen display to memory as a data file
- **Page Setup ...** - Settings for page display
- **Print ...** - actual page is printed
- **Show Point Values** – display measuring values of chart at the mouse pointer
- **Un-Zoom** – undo last Zoom
- **Undo all Zooms** – undo all Zooms
- **Set scale to Default** – reset of values in the display to factory settings



Chart




4. Chart – Analysis of fidbox measuring data



Continue with close or make a new selection ...



5. Compare Chart - Using fidbox measuring data



Bildschirmanzeige



After the read out of the **fidbox** measuring data, the required data files of two different **fidbox** units can be selected and immediately analysed by clicking on the program selection button “**Compare Chart**”.

Thus, it is possible to have two different **fidbox** elements in direct comparison and to present and to analyze with each other.


The progression of the whole measurement period can be viewed in understandable diagrams, separated by temperature levels (°C) and relative humidity (%).

Zooming in selected periods of time and movement of limits is possible at any time and without any impact on the originally stored data.

Continuation on the next page ...



5. Compare Chart - Using fidbox measuring data



Selection 1 **fidbox** file and setting of limitation values and display of measurement data

Chart with limit lines (red), divided into time frame (date) and course. Display of both sensors of the **fidbox**

Selection 2 **fidbox** file and setting limitation values and for display of measurement data.

Chart with limit lines (red), divided into time frame (date) and course. Display of both sensors of the **fidbox**

Continuation on the next page ...





5. Compare Chart - Using fidbox measuring data

Step 1:

Select for comparison charts the desired **first fidbox** measuring data file. In the scroll down menu you will find all available **fidbox measuring data** files to choose from. By clicking the desired file, the desired **fidbox** file is selected and immediately displayed for analysis.

The screenshot shows the software interface for Step 1. It includes a 'Measurement:' dropdown menu set to 'Temperature', a 'Unit:' dropdown menu set to 'Celsius', and two temperature limit fields: 'Temperature Above:' set to 26 and 'Temperature Below:' set to 17. Below these is a file selection dropdown menu showing 'fidbox-123456-Hotel-2012 4/17/2012 10:55:01 AM'. To the right of the file selection are checkboxes for 'T1:' and 'T2: Floor Material', both of which are checked. Further right are 'From' and 'to' date selection fields, with 'From' set to '12.10.2008' and 'to' set to '17.04.2012'. Two red arrows point up to these date fields.

Screen Display

Step 2:

For the data analysis evaluation time period select "Date from" and "Date to" of the desired **fidbox** measuring data file. In the scroll down menu, the factory setting will display all available **fidbox** measuring data for selection. By clicking and selecting the desired date limitations (in calendar form) the desired date limitations are selected and immediately displayed for analysis.

Tip: Note that in the field "**Date from**" you must have an earlier date than in the field: "**Date to**".

Continuation on the next page....





5. Compare Chart - Using fidbox measuring data

Step 3:

Choose what you want to first analyse in the comparison charts. Click in the field “**Measurement**” on the scroll button and select out as desired. **Temperature °C or rel. % Humidity**. This setting can be changed at any time.

(Factory setting is for temperature).

Select if required in the selection window “**Unit**” the desired fidbox temperature display “**Celsius / Fahrenheit**”. Hereby, all temperature (factory setting Celsius) will be converted accordingly and so displayed.

Step 4:

Click the scroll button and set here if required other desired values with which the data should be evaluated.

When you call-up the **fidbox** measuring data files for comparison chart analysis, the limitation value settings are displayed corresponding to your selection as upper or lower limit (red line limit).

You always have the option of adapting and change the display settings according to your wishes and adapt to change.

The factory setting is: temp above 26 °C and below temp: 17 °C or relative humidity above 60% and relative humidity below 45%.

Screen Display

The screenshot shows the software's configuration window. At the top, there are two dropdown menus: 'Measurement' set to 'Temperature' and 'Unit' set to 'Celsius'. To the right of these are two input fields for temperature limits: 'Temperature Above: 26' and 'Temperature Below: 17'. Below the 'Measurement' dropdown is a file selection dropdown showing 'fidbox-123456-Hotel-2012 4/17/2012 10:55:01 AM'. To the right of the file dropdown are two checkboxes, 'T1' and 'T2: Floor Material', both of which are checked. To the right of the 'T2' checkbox is a date range selector with 'From' and 'to' labels, showing dates '12.10.2008' and '17.04.2012' respectively. Two red arrows originate from the text above: one points to the 'Measurement' dropdown and the other points to the 'Unit' dropdown.



Continuation on the next page ...



5. Compare Chart - Using fidbox measuring data

Measurement: Temperature Unit: Celsius Temperature Above: 26 Temperature Below: 17

fidbox-123456-Hotel-2012 4/17/2012 10:55:01 AM ☒ T1: ☒ T2: Floor Material From 12.10.2008 to 17.04.2012

Screen Display

Step 5: - if desired

By activating or deactivating the display of a measuring sensor it can be shown or hidden. With set tick mark (factory setting), the respective sensor measurement is presented as a graph in the display.

T1: Substrate sensor as a **green line** __

T2: Floor Material sensor as a **black line** __


You always have the option to change this display to your liking.

Continuation on the next page ...





5. Compare Chart - Using fidbox measuring data



Screen Display

Step 6:

Complete the selections and settings for the second fidbox as well for comparison charts. This allows you to analyze both selected fidbox data sets in a direct comparison.

You always have the option to change this display to your liking.

Continuation on the next page ...





5. Compare Chart - Using fidbox measuring data




Diagram analyze Temperature °C




Diagram analyze rel. Humidity %





Diagram section – Zoom




Context menu with the right mouse button




Compare Chart



5. Compare Chart - Using fidbox measuring data




Continue with Close or make a new selection ...





6. Init-fidbox – fidbox search, read-out, and change setting



Initializing the fidbox

The Init **fidbox** button includes a lot of options. You can read the **fidbox** measurement data via RF or magnetic search or call up already stored data.

You can also check the settings of the **fidbox** or make required changes.

Since this is a very complex category, we have created a separate manual. Please click on the button “manual” and select “Setting **fidbox**” or use our separate Manual 3 “Initializing the **fidbox**”.



7. Report – Creating report using measuring data

The screenshot shows the 'fidbox - Electronic Monitoring System' window. The 'Report 1' form is displayed, featuring a red sidebar with navigation buttons: Sync, Table, Chart, Compare Chart, int fidbox, Report, Delivery Note, Handheld Tools, Manual, Info, and Close. The main form area contains several sections:

- Compiler Info:** Name (fidbox Team), Address (Außermanzing 28), City, State, Zip (A-3033 Allengbach), Phone (+43 - (0) 2774 - 6747-0), Date (5/25/2013), and a 'Choose Company Logo' button.
- Transmission Type:** Transmitter, Data reception, and Data read-out fields.
- Device Data:** Handheld ID (00904700CB4201083053433), Owner, Read-out date (17.04.12 10:55:01), Software Version (fidbox mobile V3.5.0.11), and File Version (1.0.0).
- Limitation Value:** Temperature (min. < 17°C / max. > 26°C) and Humidity (min. < 45% / max. > 60%).
- Signature Data:** Location, Date (5/25/2013), Stamp, Signature (Helmut Jilg, floor), Evaluation (checked), Show Data Table (checked), and a Report dropdown menu.
- Installer Data:** Company, Contact Person, Address, City, State, Zip, Phone, and Others fields.
- Project Data:** Builder, Contact Person, Address, City, State, Zip, Phone, and Others fields.
- Subfloor/Underfloor Heating:** Substrate Preparation, Primer Manuf., Levelling Compound Manuf., Installation Type, Adhesive Type/Manuf., Wood Type/Manuf., Type-construction, Product Description, First Maintenance/Manuf., and Date of Installation.
- Actual Room Temperature:** Actual Room Temperature and Actual Room Humidity fields.

At the top of the form, there are buttons for 'Clear all fields', 'Chart', 'Create Report', 'Copy', and 'Close'.

The creation of reports

After completing the Read-Out of a **fidbox** the measurement data can be immediately selected and evaluated in a report form by clicking on the program selection button “Report”.

You can individually chose the scope of the report by date coverage limitations and evaluation report with or without individual measurement data.

The report output has a multiple of options to choose from e.g. it can be sent direct to the printer or as a PDF file.

The reporting for **fidbox** measurement data files can be repeated as often as you wish – even with changed settings.

As this subject requires more detail you will find a separate manual for this purpose. Please click the button “Manual” and open “Creating Reports”

Continuation on the next page ...





8. Consignment note

Supply Note 1

Company: _____

Pos.	Zeitstempel	UID	Intervall	Einheit	Tempera	Hum
1	3/15/2013 6:27 AM	E004201104102332	00:08	SEKUND...		
2	3/29/2013 12:25 PM	E004201104102113	00:03...	SEKUND...		

Orange Row - One value is outside the range

Location, Date: 5/25/2013

Company stamp, _____

Create Supply Note

Delivery note-Supply note


After the initialization of a **fidbox** is complete there is the possibility to create a delivery note.

The programmed data and the respective **fidbox** serial number will be included in a so called supply note.

An explanation of how to prepare the delivery note can be found by clicking on the button “manual” and select the category “Initializing the **fidbox**” or our separate Manual 3 - Initializing the **fidbox**



9. Handheld




Handheld

This function is intended for those who have their own handheld. It is used to synchronize your handheld with your computer. On the one hand it can update the software on your handheld and on the other hand it can transfer the read-out data of a **fidbox** using a handheld **fidbox** to the computer. For this subject, we have created a separate manual. To learn more, just click on the select button "Manual" and click again on "Updates for Handheld Software" or use our separate manual 5 software update for the handheld.



10. Manual – Detailed Explanations

Manuals for detailed Information



The section “**Manual**” will provide prompt access to this manual as well as other more detailed manuals regards specific subjects.

Continuation on the next page ...






12. Close – Leave the program

Leave the program

By clicking the “**Close**” button, the program will close immediately and you will return to your desktop.

Continue with Close or a make new selection ...



Close



fp floor protector GmbH
Außermanzing 28
A-3033 Altlengbach, Austria
Phone: +43 - (0) 2774 - 29701
Fax: +43 - (0) 2774 - 29701-19
office@floorprotector.at
www.floorprotector.at

floor protector®

Safe from the Ground up.